

XHD FASTENER (#15)

# DESCRIPTION-

The CinchGrip #15 Screws are designed to be used with Roofing Insulation and Membrane Plates to secure ridged insulation, EPOM, TPO, or PVC, to steel or wood solid concrete structural decks. Fasteners ranging in length from 1.25" to 14" are available to meet a variety of commercial roofing applications.

### METHOD OF APPLICATION:

USING THE #3 Phillips tip provided and a variable speed

drill, engage the fastener into the deck as noted below. Do not over or under drive the fastener. Threads must engage the decking material per technical specifications.

- DETERMINE SCREW LENGTH AS FOLLOWS:
  - Steel Decks: Select fastener length to penetrate through the deck a min of 3/4 (191.mm)
  - . Wood Decks: Select fastener length to penetrate into or through the deck a minimum of 1" (25.4mm)

3RDPARTYIN	DEPENDENT
LAB: TEST	ING DATA
	Decule

ASTM F606/ F606M-2019	Results
Tensile	5235 lbf
Shear Test	3035 lbf
Torque Test	182 lbf
ASTM B117	Less than 15% Red
Pull Out Test	Rust
22,20,18 Ga Steel Deck	610+ lbf

#### **PROPERTIES**

Material: SAE1022 HEAT TREATED STEEL

Coating/Diameter: CR-10/ 6.8mm

High Performance Drill Point Fastener Tip:

Fastener Head: #3 Phillips Drive

Size & Quantities					
Serew Length	Thread Length	Pieces per Box	Per Package	Packages per Pallet	
11/4" (32 mm)	FULL	1,000	20 Lbs	60	
2" (50 mm)	FULL	1,000	23 Lbs	60	
3" (75 mm)	FULL	1,000	32 Lbs	60	
4" (100 mm)	3" (76.2 mm)	1,000	41 Lbs	60	
5" (125 mm)	4" (101.6 mm)	1,000	50 Lbs	60	
6" 160 mm)	4" (101.6 mm)	500	31 Lbs	60	
7" (180 mm)	4" (101.6 mm)	500	35 Lbs	60	
8" (200 mm)	4" (101.6 mm)	500	39 Lbs	60	
9" (230 mm)	4" (101.6 mm)	500	43 Lbs	60	
10" (254 mm)	5" (127 mm)	500	50 Lbs	48	
12" (305 mm)	5" (127 mm)	500	59 Lbs	48	
14" (355 mm)	5" (127 mm)	500	69 Lbs	48	

#### STORAGE:

Store in original, unopened packaging protected from the weather.

#### PRECAUTIONS:

Eye and hand protection must be worn during the installation of the fasteners.



Size	Part #	Color	
11/4" (32mm)	CINCHGRIP -CG15-1.25INB	Black	
2" (50mm)	CINCHGRIP -CG15-2INB	Black	
3" (75mm)	CINCHGRIP -CG15-3INB	Black	
4" (100mm)	CINCHGRIP -CG15-3INB	Black	
5" (125mm)	CINCHGRIP -CG15-4INB	Black	
6" (160mm)	CINCHGRIP -CG15-5INB	Black	
7" (180mm)	CINCHGRIP -CG15-6INB	Black	
8" (200mm)	CINCHGRIP -CG15-7INB	Black	
9" (230mm)	CINCHGRIP -CG15-8INB	Black	
10" (255mm)	CINCHGRIP -CG15-10INB	Black	
11" (305mm)	CINCHGRIP -CG15-12INB	Black	
14" (355mm)	CINCHGRIP -CG15-14INB	Black	

## CINCH TECH LLC. PRODUCTS AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Neither Cinch Tech LLC nor its representatives practice architecture/engineering. Cinch Tech LLC offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. CinchTech LLC accepts no liability for structural failure or resultant damages. Consult a structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Cinch Tech LLC representative is authorized to vary this disclaimer.

