CINCHTECH





The CinchGrip #15 Screws are designed to be used with Roofing Insulation and Membrane Plates to secum ridged Insulation, EPOM, TPO, or PVC, to steel or wood solid concrete structural decka. Fasteners ranging in length from 1.25 to 14" are available to meet a variety of commercial roofing applications.

METHOD OF APPLICATION:

USING THE #3 Phillips tip provided and a variable speed drill, engage the fastener into the deck as noted below. Do not over or under drive the fastener. Threads must engage the decking material per technical specifications

DETERMINE SCREW LENGTH AS FOLLOWS:

- Steel Decks: Select fastener length to penetrate through the deck a min of 3/4 (191 mm)
- Wood Decks: Select fastener length to penetrate into or through the deck a minimum of 1" (25.4mm)

Size & Quantities					
Serew Length	Thread Length	Pieces per Box	Per Package	Packages per Pallet	
11/4" (32mm)	FULL	1,000	20 Lbs	60	
2" (50mm)	FULL	1,000	23 Lbs	60	
3" (75mm)	FULL	1,000	32 Lbs	60	
4" (100mm)	3" (76.2 mm)	1,000	41 Lbs	60	
5" (125mm)	4" (101.6 mm)	1,000	50 Lbs	60	
6" (160mm)	4" (101.6 mm)	500	31 Lbs	60	
7" (180mm)	4" (101.6 mm)	500	35 Lbs	60	
8" (200mm)	4" (101.6 mm)	500	39 Lbs	60	
9" (230mm)	4" (101.6 mm)	500	43 Lbs	60	
10" (254mm)	5" (127 mm)	500	50 Lbs	48	
12" (305mm)	5" (127 mm)	500	59 Lbs	48	
14" (355mm)	5" (127 mm)	500	69 Lbs	48	

STORAGE:

Store in original, unopened packaging protected from the weather.

PRECAUTIONS:

Eye and hand protection must be worn during the installation of the fasteners.



CINCHGRIP

XHD FASTENER (#15)

3RD PARTYINDEPENDENT **LAB: TESTING DATA**

ASTM F606/ F606M-2019	Results	
Tensile	5235 lbf	
Shear Test	3035 lbf	
Torque Test	182 lbf	
ASTM B117	Less than 15% Red	
Pull Out Test	Rust	
22,20,18 Ga Steel Deck	610+ lbf	

PROPERTIES

SAE 1022 HEAT TREATED STEEL Material: Coating/Diameter: CR-10 / 6.8mm Fastener Tip: **High Performance Drill Point** #3 Phillips Drive Fastener Head:

CINCHGRIP XHD (#15) FASTENER

Size	Part #	Color
11/4" (32mm)	CINCHGRIP -CG15-1.25INB	Black
2" (50mm)	CINCHGRIP -CG15-2INB	Black
3" (75mm)	CINCHGRIP -CG15-3INB	Black
4" (100mm)	CINCHGRIP -CG15-3INB	Black
5" (125mm)	CINCHGRIP -CG15-4INB	Black
6" (160mm)	CINCHGRIP -CG15-5INB	Black
7" (180mm)	CINCHGRIP -CG15-6INB	Black
8" (200mm)	CINCHGRIP -CG15-7INB	Black
9" (230mm)	CINCHGRIP -CG15-8INB	Black
10" (255mm)	CINCHGRIP -CG15-10INB	Black
12" (305mm)	CINCHGRIP -CG15-12INB	Black
14" (355mm)	CINCHGRIP -CG15-14INB	Black

CINCH TECH LLC. PRODUCTS AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Neither Cinch Tech LLC nor its representatives practice architecture/engineering. Cinch Tech LLC offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. CinchTech LLC accepts no liability for structural failure or resultant damages. Consulta structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Cinch Tech LLC representative is authorized to vary this disclaimer.









