

## FLEXBOND™ LOW-RISE FOAM ADHESIVE

McGuire FlexBond™ is a two-component, expanding foam adhesive/sealant designed for the installation of all types of foam roofing insulation and fleece backed roofing membranes. Apply to wood, concrete, gypsum and metal decks.

### APPLICATION

Surfaces must be clean and dry. Apply at any temperature. High temperatures and humidity will shorten working time. Designed for use at temperatures of 20F and higher. Very cold temperatures will result in less rise and slower cure. Cut the tip of the static mixer to the desired side. Remove the red plug from the cartridge and install the static mixer in its place. Apply in ribbons ¼” to ½” wide a maximum of 12 inches on center (oc). Coverage at 12” oc is approximately 150 sq. ft. per cartridge. One case will adhere approximately 600<sup>ft2</sup> of insulation or membrane.

Install the insulation board while the adhesive is still tacky. Insulation boards should be 48” x 48” or smaller for best results. Weight if necessary in windy conditions. Avoid traffic for 24 hours.

Clean up: Clean up with McGuire Seam Cleaner

Shelf life: One year from the date of manufacture. Store in a cool dry place. High temperatures and high humidity during storage will shorten the product’s shelf life.

CAUTION: Do not take internally. If swallowed, do not induce vomiting. Keep out of reach of children. Read SDS prior to use.

Container Sizes: 1500ml two component cartridge (4 per case including 6 mixing nozzles), 5-gallon bag in a box (10 gallon kit)

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of ONE YEAR from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application. LIMITATION OF LIABILITY: In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller’s option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.

NOTE: Some or all of the foregoing may not apply or may be invalid under the laws applicable to Buyer’s purchase or claim. Consult local law to determine the applicability of any of the foregoing in the event of any defect or failure of this product.

### FLEXBOND SPECIFICATIONS

|                   |             |  |
|-------------------|-------------|--|
| Solids by Weight  | ASTM D 1644 | Part A 100%<br>Part B 95%<br>(5%water) |
| Solids by Volume  | ASTM D 2697 | Part A 100%<br>Part B 95%              |
| Weight Per Gallon | ASTM D 1475 | 8.98lbs/gal<br>(mixed)                 |
| Tack Free time    | ASTM C 679  | ~20 min @<br>70F                       |
| Flash Point       | ASTM D56    | >150C                                  |
| VOC               | EPA 24      | none                                   |